

The global leader in
door opening solutions

Rockwood 555 - Lever Extension Flush Bolt



Specifications:

MATERIAL:

Brass

FASTENERS:

8 ea. #8 x 3/4" Flat Head Combo Screws

FEATURES:

- For Fire Rated Hollow Metal Swinging Doors measuring up to 4'w x 10'h rated up to and including 3 Hours
- Fits ANSI A115 door and frame preparation
- 3/4" bolt throw, 3/4" rod backset
- 12" rod length (center of face to bolt end - retracted)
- 1 1/2" adjustable bolt head

OPTIONS:

- Other size rods available are 18", 24", 36", 48"
- Extra long bolt head - 2 1/2" (or to your specification)
- Use #570 Dust Proof Strike to prevent dirt blocking bottom strike



Available Finishes:

- US3/605
- US4/606
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626

SIZE:

Face Plate: 1" x 6 3/4"

Strike: 15/16" x 2 1/4"

Guide: 1" x 2"

WEIGHT:

1.5 lbs./2

ANSI A156.16:

L04251

300 Main Street

Rockwood, Pennsylvania 15557

P: 800.458.2424 • F: 800.922.9212

www.rockwoodmfg.com • orders.rockwood@assaabloy.com

Copyright © 2017, Rockwood Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Rockwood Manufacturing Company is prohibited.