

A
Hinges & pivots



DP1

B
Pulls & plates



DP2

C16
Flush bolts & coordinators

D
Latches, catches & bolts

E
Stops

F
Exterior hardware

G
Miscellaneous hardware

DP1 Dust proof strike - round face plate

DP2 Dust proof strike - rectangular face plate

- Designed for use with the bottom bolt of all flush bolts.
- Spring-loaded plunger returns to floor or threshold level anytime flush bolt is retracted, eliminating need to clean standard floor strikes.
- Strike hole is 3/4" diameter and 1-1/8" deep

Certifications

- Meets ANSI A156.16, L14011

Mounting

- 8-32 X 1" FPHMS

Dimensions

DP1 Face Plate (Diameter)	DP1 Face Plate (Width X Length X Thickness)	Body: (Diameter X Depth)
1-7/16"	1-5/8" x 3-1/2" x 1/8"	1-3/16" x 1-7/8"

Finishes

BHMA	Description	Substrate	US
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
612	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
619*	Satin nickel	Brass	US15
622*	Matte black	Brass	BLK
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D
643e/716*	Aged bronze	Brass	-

*Finishes only available with DP2

Custom finishes are available as engineering special, consult customer service

Available accessory items

- Security pin screws