



FB358 Top or bottom bolts

- When the active door is opened, the lever can be moved to the 'up' position, retracting the bolt and allowing the inactive leaf to be opened. When the inactive leaf is closed, the lever can be moved to the 'down' position, projecting the bolt into the strike and securely locking the inactive leaf
- Reduces installation costs; requires only simple router mortise at top and bottom corners of doors
- Door strength and rigidity maintained by tying door faces to reinforcing extensions on guide with machine screws and bearing washers, not supplied
- Non-handed
- Bolt tip 1/2" diameter
- Bolt throw is 3/4" with a 7/8" vertical adjustment
- Bolt backset is 3/4"
- Not available for rabbeted door installations

Certifications

- Meets ANSI A156.16, L04261
- UL Listed 90 Minute fire doors 8'0" X 10'0". Fire rated openings require top and bottom bolt.

Mounting

- 8 X 1" FPHSMS
- 8 X 3/4" FPHSMS

Dimensions

| Body size (Width X Length X Depth) | Guide Size (Width X Length X Thickness) | Strike size (Width X Length X Thickness) |
|---------------------------------------|--|---|
| 1" x 6-3/4" x 1-3/8" | 1" x 2-1/2" x 5/64" | 15/16" x 2-1/4" x 5/64" |

Finishes

| BHMA | Description | Substrate | US |
|----------|-------------------|-----------|-------|
| 605 | Bright brass | Brass | US3 |
| 606 | Satin brass | Brass | US4 |
| 612 | Satin bronze | Brass | US10 |
| 613 | Oil rubbed bronze | Brass | US10B |
| 619 | Satin nickel | Brass | US15 |
| 622 | Matte black | Brass | BLK |
| 625 | Bright chrome | Brass | US26 |
| 626 | Satin chrome | Brass | US26D |
| 643e/716 | Aged bronze | Brass | - |

Custom finishes are available as engineering special, consult customer service.

Available accessory items

- DP1 and DP2 dust proof strike, see page C16

Hinges & pivots
A

Pulls & plates
B

Flush bolts & coordinators
C13

Latches, catches & bolts
D

Stops
E

Exterior hardware
F

Miscellaneous hardware
G