



**U696 One-way viewer - UL**

- 150° angle of view
- For doors 1-3/8" to 2-1/16" thick
- Secure, tamper-resistant one-way thread installation
- Simple installation — only a 1/2" hole required
- Suggested installation height: 60" from floor

**Material substrate**

- Meets ANSI/BHMA A156.16, L23222
- UL listed 90 minute fire doors

**Dimensions**

- External diameter: 3/4"

**Available accessory items**

- Trim washer available, 3/4" x .032" thick.
- Extensions available for thicker doors
- Privacy viewer covers to prevent viewing from outside the room

**Finishes**

BHMA	Description	Substrate	Finish
606	Satin brass	Brass	B4
613	Oil rubbed bronze	Brass	B10B
619	Satin nickel	Brass	B15
622	Matte black	Brass	B-BLK
625	Bright chrome	Brass	B26
626	Satin chrome	Brass	B26D
---	Aged bronze	Brass	B-643e/716

*For other colors, consult factory.*



**698 One-way wide angle viewer**

**U698 One-way wide angle viewer - UL**

- 190° angle of view
- 4 optical glass lenses
- For doors 1-3/8" to 2-1/8" thick
- Simple installation — only a 9/16" hole required
- Suggested installation height: 60" from floor

**Material substrate**

- Meets ANSI/BHMA A156.16, L23222
- U698 is UL listed 90 minute fire doors

**Dimensions**

- External diameter: 1"
- Lens projects 1/4" from face of door

**Available accessory items**

- Extensions available for thicker doors
- Privacy viewer covers to prevent viewing from outside the room

**Finishes**

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	B3
619*	Satin nickel	Brass	B15
622*	Matte black	Brass	B-BLK
625*	Bright chrome	Brass	B26
626	Satin chrome	Brass	B26D
---	Aged bronze	Brass	B-643e/716

*For other colors, consult factory. \*Not available on 698.*

Hinges & pivots  
**A**

Pulls & plates  
**B**

Flush bolts & coordinators  
**C**

Latches, catches & bolts  
**D**

Stops  
**E**

Exterior hardware  
**F5**

Miscellaneous hardware  
**G**